TECHNICAL SPECIFICATION

ATREYO®
SOLUTIONS THAT SIMPLIFY

Industrial LTE/GSM Modem with GNSS and DIV antenna

AM-201



Features

- **4G LTE CAT1 with fallback to 3G and GPRS**
- **GNSS optional**
- **SMS support**
- **USB, RS232, RS485 interfaces**
- **USB drivers for Linux and Windows systems**
- **Wide power supply range up to 36V**
- **DIN rail mounting**
- **Aluminium enclosure**

This is 4G LTE Cat1 modem for use in industrial environment. It communicate to host by USB, RS485 and RS23. The modem has diversional and GNSS antenna options. For use in IoT systems, industrial control systems, electrical panels and distribution systems, public display controllers, remote monitoring for agriculture and industrial IoT.

Description	Parameter
Cellular Specification	
Cellular bands	Refer Cellular specification chart
SIM card	3V/1.8V
SIM card holder	MicroSIM, push-pull type holder
Antenna Connector	SMA female
DIV antenna	SMA female[1]
USB	
USB port number	1
USB	2USB 2.0
Connector	USB type B
Protection	IEC 61000-4-2 level 4: – 15 kV (air discharge) – 8 kV (contact discharge)
Serial RS485	
Port number	1
Interface Type	RS485
Data Rate	4800, 9600, 19200, 38400, 57600, 115200, 230400, 460800 and 921600 bps baud rates The default is 115200 bps
Signals	A, B and common ground
Connector	Pluggable screw socket
Protection	IEC 61000-4-2 level 4: – 15 kV (air discharge) – 8 kV (contact discharge)
Serial RS232	
Port number	1
Data Rate	4800, 9600, 19200, 38400, 57600, 115200, 230400, 460800 and 921600 bps baud rates, The default is 115200 bps
Signals	RX, TX and common ground
Connector	Pluggable screw socket
Protection	ESD Protection Exceeds ±15 kV Using Human-Body Model (HBM)
GNSS[2]	
GNSS Systems	GPS, BAIDOU (GPS / GLONASS /

1 GL model only

Description	Parameter
GNSS	
	BDS / Galileo)
Antenna Connector	SMA female
Antenna type	Active 3.3V antenna support
System Functions Indicators	
Indicators	ON, ACT, LTE (GNSS antenna power in GL version)
System	
To work on USB	Linux, Windows
To work by serial	All systems by AT commands
Power Supply	
Power Voltage range	8-36V DC
Power consumption	1W average
Connector	2 pin (+, -) pluggable screw socket
Protection	Reverse polarity, surge
Physical Characteristics	
Installation	DIN-Rail, clamp
Housing	Aluminium
Weight	190g
Dimensions	88mm x 65mm x 35mm
Environmental Specification	
Operating temp.	-20 ~ 65°C (-4 ~ 149°F)
Storage temp.	-40 ~ 85°C (-40 ~ 185°F)
Ambient RH	5% to 95% (non-condensing)

2 GL model only

Cellular specification of IN (India) version of Modem

EU version of gateway	Cellular network interface details	
Band LTE FTD	B1/B3/B5/B8	
Band LTE TDD	B34/B38/B39/B40/B41	
WCDMA	B1/B5/B8	
Band GSM/EDGE	B3/B8	
GPRS slot	Multi-slot class 12/10	
Bandwidth	1.4/ 3/ 5/ 10/ 15/ 20 MHz	
Output power	LTE-FDD	Class 3 (23 dBm ±2 dB)
	LTE-TDD	Class 3 (23 dBm ±2 dB)
	EGSM900	Class 4 (33 dBm ±2 dB)
	DCS1800	Class 1 (30 dBm ±2 dB)
Maximum data rate LTE	LTE-FDD	150 Mbps (DL), Max. 50 Mbps (UL)
	LTE-TDD	130 Mbps (DL), Max. 30 Mbps (UL)
Maximum data rate UMTS	DC-HSDPA	21 Mbps (DL)/ 5.76 Mbps (UL)
	WCDMA	384 kbps (DL), Max. 384 kbps (UL)
Maximum data rate GSM	EDGE	236.8kbps (DL), Max. 236.8 kbps (UL)
	GPRS	85.6 kbps (DL), Max. 85.6 kbps (UL)
Power	Compliant to GSM phase 2/2+	
	– Class 4 (2 W 900MHz)	
	– Class 1 (1 W 1800MHz)	

Cellular specification of GL (global) version of Modem

GL version of gateway	Cellular network interface details	
Band LTE FTD	B1/B2/B3/B4/B5/B7/B8/B12/B13/B18/B19/B20/B25/B26/B28	
Band LTE TDD	B38/B39/B40/B41	
Band WCDMA	B1/B2/B4/B5/B6/B8/B19	
Band GSM	B2/B3/B5/B8	
Output power	GSM850	Class 4 (33 dBm ±2 dB)
	EGSM900	Class 4 (33 dBm ±2 dB)
	DCS1800	Class 1 (30 dBm ±2 dB)
	PCS1900	Class 1 (30 dBm ±2 dB)
	GSM850 8-PSK	Class E2 (27 dBm ±3 dB)
	EGSM900 8-PSK	Class E2 (27 dBm ±3 dB)
	DCS1800 8-PSK	Class E2 (26 dBm ±3 dB)
	PCS1900 8-PSK	Class E2 (26 dBm ±3 dB)
	WCDMA	Class 3 (24 dBm +1/-3 dB)
	LTE-FDD	Class 3 (23 dBm ±2 dB)
	LTE-TDD	Class 3 (23 dBm ±2 dB)
Maximum data rate LTE	LTE-FDD	150 Mbps (DL), Max. 50 Mbps (UL)
	LTE-TDD	130 Mbps (DL), Max. 30 Mbps (UL)
Maximum data rate UMTS	DC-HSDPA	42 Mbps (DL)
	HSUPA	5.76 Mbps (UL)
	WCDMA	384 kbps (DL), Max. 384 kbps (UL)
Maximum data rate GSM	EDGE	296 kbps (DL), Max. 236.8 kbps (UL)
	GPRS	107 kbps (DL), Max. 85.6 kbps (UL)

Standard model list

Model	Hardware Options				More information
AM-201	Cellular Network			GNSS	
	GPRS	3G	LTE		
AM-201-IN	✓	✓	✓		
AM-201-GL	✓	✓	✓	✓	

For more details scan or click on QR code

Copyright

Copyright © 2026 Atreyo Research and Development Pvt. Ltd. This technical specification is protected under national and international copyright laws. No part of this user manual may be reproduced, distributed, translated, or transmitted in any form or by any means, electronic or mechanical, including photocopying, recording, or storing in any information storage and retrieval system, without the prior written permission of Atreyo Research and Development Pvt. Ltd.. Copy or use any part of this specifications is prohibited without the prior written permission from the Atreyo Research and Development Pvt. Ltd.

Trademarks

Atreyo and the Atreyo logo are registered trademarks of Atreyo Research and Development Pvt. Ltd.

All other trademarks and copyrights are the property of their respective owners.

Disclaimer

- The information contained in this Technical Specification is provided "as is" and is subject to change without notice. While every effort has been made to ensure the accuracy and completeness of the information contained herein, Atreyo Research and Development Pvt. Ltd. assumes no responsibility or liability for any errors or omissions.
- Images used in this specification may differ in appearance from the actual product.
- All dimensions mentioned in the drawings are not to scale and are subject to change and update as may be decided by the Atreyo Research and Development Pvt. Ltd.
- Atreyo Research and Development Pvt. Ltd. makes no warranties, either express or implied, regarding the contents of this document, including but not limited to the implied warranties of merchantability and fitness for a particular purpose.
- Users of this Technical Specification should verify the applicability and suitability of the information and procedures to their particular use. Atreyo Research and Development Pvt. Ltd. shall not be liable for any damages, including but not limited to direct, indirect, special, incidental, or consequential damages, arising from or related to the use or inability to use this Technical Specification or the products described herein.
- By using this Technical Specification, you agree to the terms and conditions stated above. Atreyo Research and Development Pvt. Ltd. has right to make additions, deletions, alterations or amendments as and when it deems fit and proper, without any prior notice.
- The Atreyo Research and Development LLP reserves rights to make additions, deletions, alterations or amendments as and when it deems fit and proper, without any prior notice.

Atreyo Research & Development Pvt. Ltd.	+91 9727741417 info@atreyo.in	2106, Z2, Thaltej, Ahmedabad, Gujarat, India